	SCR-1	SCR-2	ISL-32
	SOLED ON	SCUECE DE SOLED SO	The Branch of the land of the
VOLTAGE	12 - 24 V	12 - 24 V	5 - 24 V
MAX OUTPUT	200 W	200 W	32 x 1A 🔽
DIMENSIONS (MM)	103 x 87 x 66	140 x 89 x 63	86 x 86 x 25.5
LIGHT ON EFFECT	all together	cascade one by one	 cascade one by one follow 5 inverse cascade
LIGHT OFF EFFECT	all together	all together	off one by oneoff all together
NUMBER OF STEPS	Up to 200W 🔽	2-20	8 - 32 + Addressable LEDs
LED TYPE	Constant voltage, single colour, dimmable	Constant voltage, single colour, dimmable	constant voltage 1-32 output: single colour, dimmable addressable LED output: RGB addressable LED
DIN RAIL COMPATIBLE	Yes	Yes	No
WARRANTY	2 years	2 years	2 years
ADDITIONAL FEATURES	 brightness and duration adjustment three types of motion sensor options several LED light options several LED channel options optional extras (digital timer, enclosure, extension wires, quick connectors) 	brightness, speed and duration adjustment three types of motion sensor options several LED light options several LED channel options optional extras (digital timer, enclosure, extension wires, quick connectors)	 brightness, speed+duration adjustment daylight sensor OLED display 4 main operation modes various colour modes damaged CV channels can be disabled two controllers can be connected for dual cascading effect (2 x 32 steps)
INCLUDED IN THE KIT	All kits: controller 2 x motion sensors (with 10 m wire each) Optional extras: power supply LED srips or spotlights LED channels digital timer extension wires quick connectors	All kits: controller 2 x motion sensors (with 10 m wire each) Optional extras: power supply LED srips or spotlights LED channels digital timer extension wires quick connectors	All kits: Controller 2 x wide detection angle motion sensors 2 x narrow detection angle motion sensors 2 x 5m wire for the motion sensors Optional extras: flush-mount sensors Important note: compatible power supplies and LED strips need to be purchased separately!